

**BS SPECIFICATIONS**

- Suitable for industrial applications
- Double chassis with one loadcell steel platform
- Overload and shock resistance
- Understandable LED warnings
- Automatic power protection, shut down mode
- Internal Rechargeable battery and 220V AC connection
- Automatic zeroing, tare adjustment
- RS 232 Communication
- Crystal Vision Wide Angle LCD Display with LED Backlight
- Flexible Indicator Mounting Design
- High Speed 24 bits Multiplexed Delta-Sigma A/D Converters
- 2 years of warranty, spare part and repair support
- Manufacturability in desired size and capacity



**OPTIONAL FEATURES**

- Thermal label printer
- External display
- Wireless connection
- Stainless steel platforms and load cells.

Trade Approved / Dual Weighing Range



MODEL: BS / Bench Scale		
MODEL	CAPACITY	DIMENSIONS (cm)
BS	30/60 kg x 10/20 g	35x40 , 40x50
BS	60/150 kg x 20/50 g	35x40 , 40x50 , 50x60
BS	150/300 kg x 50/100 g	50x60,60x80,70x80
BS	300/600 kg x 100/200 g	60x80,70x80,80x90
BS	600/1000 kg x 200/500 g	90x110,120x120
BS	600/1500 kg x 200/500 g	90x110,120x120

Manufacturability in desired size and capacity