

TS-1 Zemin Üstü Taşıt Kantarı

TS-1 Above Ground Truck Scale

Ürün Kodu: TUNA TS-1



AÇIKLAMA / EXPLANATION

Tuna TS-1 Modeli, altyapı gerektirmeyen, kendinden rampalı mobil kantar yanında, stok sahalarında, fabrika girişlerinde, hammadde alış-satış kantarı olarak kullanılır. Zemin üzerine monte edilir. Betonarme rampaları ile kantarın üzerine çıkılır. Kantar 3 parça ve rampalardan oluşmaktadır. Sağ ve sol çelik platform içi beton loblardan oluşur. Yapısı Sağlam ve uygun maliyeti ile ön plana hükümleri. Kantar kapasitesinin %150 fazlası tartım görevlileri göre maksimum mukavemet hesaplanarak üretilmektedir.

Tuna TS-1 Model is used as a raw material purchase-sales scale in stock areas, factory entrances, as well as mobile scales that do not require infrastructure, self-ramping. It is mounted on the ground. With reinforced concrete ramps, it is possible to reach the scale. The scale consists of 3 parts and ramps. It consists of concrete lobes inside the right and left steel platform. Its structure is solid and its provisions to the fore with affordable cost. More than 150% of the scale's capacity is produced by calculating the maximum strength according to the weighing officers.

Specifications

- 1/30000 A/D conversion rate
- Powerful anti-vibration software
- Zero tracking and automatic and manual reset interval
- Digital filtering setting
- Low battery warning and auto shut off when battery runs out

Technical Specifications LOAD CELL FEATURES

Depending on the size of the scale, 4 to 10 load cells are used, each working in compression type, with a capacity of 30 tons. With its stainless steel body, it is highly resistant to corrosion and has worked smoothly in harsh industrial conditions for many years. Standard mounting kits provide full protection against lateral loads. OIML R60 C4 approved and IP68 protection class.

SCALE PROGRAM

Tuna Windows-based scale program is simple to use by anyone who knows how to use a computer, but with its powerful database, advanced reporting, exporting data as XML, excel, pdf, html, and txt, combining the data of remote scales at a central point with the web report module, waste calculation Easy weighing of fixed-tare vehicles, light management system and camera and plate reading system can be integrated into the program.

Özellikler

- 1/30000 A/D çevrim hızı
- Güçlü anti vibrasyon yazılımı
- Sıfır takibi ve otomatik ve manuel sıfırlama aralığı
- Dijital filtreleme ayarı
- Düşük batarya uyarısı ve batarya bittiğinde otomatik kapanma

Teknik Özellikler LOAD CELL ÖZELLİKLERİ

Baskı tipte çalışan her biri 30 ton kapasitede, kantarın büyüklüğüne göre 4 ila 10 adet arasında load cell kullanılır, Paslanmaz çelik gövdesi ile korozyona karşı son derece dayanıklı olup zorlu endüstri şartlarında uzun yıllar sorunsuz çalışır, standart olarak sunulan montaj kiti yan yükler için tam koruma sağlar. OIML R60 C4 onaylı ve IP68 koruma sınıfındadır.

KANTAR PROGRAMI

Tuna windows tabanlı kantar programı bilgisayar kullanmayı bilen herkesin kolayca kullanabileceği basitlikte olmakla beraber güçlü veri tabanı ile gelişmiş raporlama, xml, excel, pdf, html, txt olarak veri dışarı atma, web rapor modülü ile birbirinden uzak kantarların verilerini merkezi bir noktada birleştirme, fire hesaplaması, sabit daralı araçları kolayca tartabilme, ışık yönetim sistemi ve kamera ile plaka okuma sistemi programa entegre edilebilir.

MODEL	DIMENSIONS (m.)	LOADCELL (ADET)	CAPACITY (TON)	TAXIMAT(KG)
TS-1-364	3X6	4	40 T	20KG.
TS-1-384	3X8	4	40-50-60 T	20KG.
TS-1-3106	3X10	6	40-50-60 T	20 KG.
TS-1-3126	3X12	6	40-50-60 T	20 KG.
TS-1-3146	3X14	6	60-80 T	20-50 KG
TS-1-3168	3X16	8	60-80-100 T	20-50 KG.
TS-1-3188	3X18	8	60-80-100 T	20-50 KG.
TS-1-3208	3X20	8	60-80-100 T	20-50 KG.
TS-1-3228	3X22	8	60-80-100 T	20-50 KG.