

ID510 EX İndikatör Exproof Cihazı

ID510 EX Indicator Exproof Device

Ürün Kodu: ID510 EX İndikatör

AÇIKLAMA / EXPLANATION

ID510 EX İndikatör yüksek hassasiyetli ,çeşitli field/bus haberleşmelerine olanak tanıyan torbalama,paketleme,sıvı dolum,dozajlama gibi sistemlerde kullanılabilen ayrıca kimyasal ve tehlikeli alanlar için tasarlanmış farklı kutulama seçenekleri ile donatılmış endüstriyel tartım kontrolörüdür.

128×64 dot matrix ekran ,200HZ A/D örnekleme hızı,200Hz karşılaştırmalı 10 adımlı filtreleme ve yüksek anti vibrasyon özellikleri ile üstün performanslı bir indikatördür.

Standart 2 adet seri porta sahip olup (RS232 and RS232/485) çeşitli field/bus seçenekleri ile PLC ve DCS cihazlarına kolaylıkla entegre olabilir.

Elektronik kalibrasyon özelliği ile referans ağırlığa ihtiyaç olmadan kalibrasyon yapılabilir.

SLB lama type stainless steel load cell. It has wide application areas with its strong structure. Thanks to its stainless steel structure, it is used in harsh environmental conditions such as food, chemical and process applications.

ID510 EX Indicator is an industrial weighing controller with high precision, which can be used in systems such as bagging, packaging, liquid filling, dosing that allows various field / bus communications, and also equipped with different boxing options designed for chemical and hazardous areas.

It is a superior performance indicator with 128 × 64 dot matrix display, 200HZ A / D sampling rate, 200Hz comparison 10-step filtering and high anti vibration features.

It has 2 standard serial ports (RS232 and RS232 / 485) and can be easily integrated into PLC and DCS devices with various field / bus options.

With the electronic calibration feature, calibration can be done without the need for a reference weight.

SLB lama type stainless steel load cell. It has wide application areas with its strong structure. Thanks to its stainless steel structure, it is used in harsh environmental conditions such as food, chemical and process applications.

Atex Uygunluk: Exd Class: EXD ib (IallcGA)IIB T6 Gb /DIP A21 TA ,T6

Apps

- 8 Inputs / 12 Outputs (OC and Relay)
- PROFIBUS DP
- 4-20mA Analog Output
- (16-bit DAC)
- 100M LAN (TCP, UDP, MODBUS-TCP)

ID510 EX Indicator Features

- 200Hz ADC speed
- 150,000d and 600e (certified)
- RS232, RS485,100M LAN
- Green OLED dot matrix graphic display
- Ability to see weight reporting and rate at the same time as PROFIBUS DP, MODBUS_RTU, 4-20MA, MODBUSTCP
- Calibration without reference weight
- Zone : Zone 2, 22 and Div. 2 location
- Various control applications

Opsiyonlar

- 8 Inputs /12 Outputs (OC and Relay)
- PROFIBUS DP
- 4-20mA Analog Output(16-bit DAC)
- 100M LAN(TCP, UDP, MODBUS-TCP)



Uygulamalar

- Standard Tartım
- Field Bus Haberleşme
- Hedef Kontrol
- Kontrol Tartım
- Sıvı Dolum
- Torbalama
- Dozajlama

ID510 EX İndikatör Özellikler

- 200Hz ADC hızı
- 150,000d ve 600e(onaylı)
- RS232,RS485,100M LAN
- Yeşil OLED dot matrix grafik ekran
- Ağırlık raporlama ve oranı aynı anda PROFIBUS DP, MODBUS_RTU, 4-20MA,-MODBUSTCP görebilme
- Referans ağırlık olmadan kalibrasyon
- Zone : Zone 2, 22 and Div. 2 location
- Çeşitli kontrol uygulamaları

Opsiyonlar

- 8 Inputs /12 Outputs (OC and Relay)
- PROFIBUS DP
- 4-20mA Analog
- Output(16-bit DAC)
- 100M LAN(TCP, UDP, MODBUS-TCP)